

World population will reach 9 billion in next 40 years (Future demand)

Challenges to meet the Sustainable Develop goals (Current)





70 % rural population, Growth in agriculture is twice as effective




Increase agricultural production, reduce hunger




Increase efficiency in agricultural, minimize loss of resource

## Why focus on Agriculture







News & Views | Published: 07 October 2019

AGRICULTURAL TECHNOLOGY

sustainability

#### Satellites and crop interventions

Jadunandan Dash ⊠

Nature Sustainability 2, 903-904(2019) | Cite this article


136 Accesses 6 Altmetric Metrics

Lack of good-quality monitoring and evaluation data is a key barrier to large-scale uptake of agriculture interventions. Data from low-cost microsatellites have a strong potential to bridge this gap and promote sustainable intensification targets.

Information requirement varies: national to farm scale National information (yield (*gap*)): Planning -> policy Farm scale decision making: management practices Time critical, spatial coverage, easy accessible

## **Development in agriculture**





https://www.mdpi.com/2624-7402/7/3/89

## Why spectral measurements




At the heart of quantitative RS in the optical region

Characterise meaningful objects in a scene

Characterise 'reference endmembers'

Hypothesis testing

Post-launch satellite sensor calibration



## **Spectral Reflectance**




**Reflection** is measured as the ratio of the amount of radiant energy that is reflected to the total incident radiant energy falling on the surface.


**Specular Reflection-** angle of the reflected light is equal to the angle of incident light.

**Diffuse reflection** - reflected light is scattered in all directions.

Most of the surfaces are a mix of specular and diffuse reflection

A Lambertian surface reflects (diffuse reflection) light or radiation equally in all directions. e.g. talcum powder





## **Spectral Reflectance**



Incoming/Reflected	Directional	Conical	Hemispherical
Directional	Bidirectional CASE 1	Directional–conical CASE 2	Directional-hemispherical CASE 3
Conical	Conical–directional CASE 4	Biconical CASE 5	Conical-hemispherical CASE 6
Hemispherical	Hemispherical–directional CASE 7	Hemispherical—conical CASE 8	Bihemispherical CASE 9

G. Schaepman-Strub, et al., 2006, Reflectance quantities in optical remote sensing—definitions and case studies, Remote Sensing of Environment, Volume 103, Issue 1, 15.

## The bidirectional reflectance distribution function (BRDF)



... a mathematical function "relating the irradiance incident from one given direction to its contribution to the reflected radiance in another direction" (Nicodemus et al., 1977)

- an inherent property of the surface.
- conceptual, not measurable.
- a mathematical function, not a single value.

BRDF = 
$$f_r(\theta_i, \phi_i; \theta_r, \phi_r) = \frac{dL_r(\theta_i, \phi_i; \theta_r, \phi_r)}{dE_i(\theta_i, \phi_i)} [sr^{-1}].$$


Bidirectional Reflectance Factor (BRF), is BRDF normalized by the reflectance of a reference Lambertian surface, identically illuminated and observed.

## Spectral Reflectance on ground















Strong reflection of NIR

Chloroplast – site were light is captured by chlorophyll for photosynthesis





Air space exchange of CO<sub>2</sub> O<sub>2</sub> and H<sub>2</sub>O between plant and atmosphere



#### Optical region

#### Chlorophyll-a and Chlorophyll-b absorb portion of blue and red light









#### Interaction in the NIR wavelength

Occurs at the upper half of the leaf and more importantly between cell and air spaces

High reflectance








#### Red edge

**Sharp change** in reflectance

Occurrence of red edge

Red edge position (REP) is the **point of maximum slope** of the curve in red/near infrared region



Red edge position is sensitive to amount of chlorophyll content



#### Interaction in the Middle infrared waveleng


**Dominated by water absorption** 


Amount of reflectance is inversely proportional to water content

#### Three major water absorption


#### bands

- 1.4 μm
- 1.9 μm
- 2.7 μm






If you were designing a sensor solely to measure the health of the sugar beets, what wavelength range would you want the sensor to detect?




## Moving to image



In one band its hard to distinguish






Composites provide a better idea








We need to use more than one band to get more information



Two objects of identical material will appear different if they are receiving different amount of illumination.

The ratio between matching pixels in each band will remain same



The second second	O kase Mercery
Adam.	TEN AM

DN on slope facing away from Sun				
Unit	Red	NIR	R/NIR	
Α	45	60	0.75	
В	20	40	0.5	

DN on slope facing Sun			
Unit	Red	NIR	R/NIR
Α	60	80	0.75
В	30	60	0.5

### **Vegetation indices**

Better sensitivity than individual spectral bands for detection of biomass

Ideal VI "the index should be particularly sensitive to vegetative covers, insensitive to soil background, little affected by atmospheric effects, environmental effects and solar illumination geometry and sensor viewing conditions (Jackson et al., 1983)

There are a lot of vegetation indices (more than 50)

Commonly used VI

- Simple Ratio (SR)
- Normalised Difference Vegetation Index (NDVI)

Deigned to monitor specific property

- Enhanced Vegetation index (EVI)
- MERIS Terrestrial Chlorophyll Index (MTCI)

## Normalised Difference Vegetation Index (NDVI)



Proposed by Rouse et al., in 1973

The specific parameter employed is the Band Ratio Parameter (BRP) defined as the difference in the ERTS radiance value measured in bands 5 and 7, divided by their sum. The normalization procedure is used to eliminate seasonal sun angle differences and to mini-

$$NDVI = \frac{NIR - red}{NIR + red}$$

NDVI value range from -1 to +1

For vegetation NDVI typically starts from 0.1

For soil/bare ground NDVI is close to zero

What will be NDVI for water?

NDVI has been extensively used in remote sensing for a number of applications:

**Primary productivity** 


Identifying eco regions


Monitoring phenological pattern

**Assessing Season length** 

#### **Disadvantages**


- 1. Saturates at high biomass content
- 2. Influence by atmospheric noise
- 3. Very sensitive to background variation







Red edge position is point of maximum change

- ☐ Increase in chlorophyll content
  - Broadens chlorophyll absorption feature
  - ☐ Shifts REP to longer wavelength.









- 1. Derivative spectrum
- 2. Curve fitting
- 3. Langrangian interpolation
- 4. Linear interpolation

$$R_i = \frac{(R_{670} + R_{780})}{2}$$

$$REP = 700 + 40 \frac{(R_i - R_{700})}{(R_{740} - R_{700})}$$









- ☐ MTCI developed as a surrogate estimator of the Red-edge position (REP).
- Overcome the saturation effect of Red edge Position
- Easy to calculate

$$MTCI = \frac{R_{Band\ 10} - R_{Band\ 9}}{R_{band\ 9} - R_{band\ 8}} = \frac{R_{753.75} - R_{708.75}}{R_{708.75} - R_{681.25}}$$





#### November-2003



Observed Issues and Recommendations

#### New L2 products

- Need for defining new L2 land products by fully exploiting the capabilities of the MERIS instrument not available from other sensors.
  - > ESA response:
  - for the land community at present we have MGVI, NDVI, rectified reflectances at 665 and 865nm, DDV AOT, surface pressure.
  - new MERIS Terrestrial Chlorophyll Index (MTCI) will be provided in the L2 product replacing the NDVI.
  - algorithms for experimental MERIS products, i.e.LAI, fraction cover, chlorophyll content, surface reflectance under development; shall be made available in source code under the BEAM software
- Need for defining new atmospheric L2 products:
  - Aerosol path radiance at 665 nm
  - Particular Matter: PM 10
  - Aktinic fluxes

DASH, J. and CURRAN, P. J., 2004, The MERIS Terrestrial Chlorophyll Index. *International Journal of Remote Sensing*, 25, 5003-5013.



Spectral Chlorophyll Indices	Name	Formulation	References
MTCI	MERIS Terrestrial chlorophyll index	(r740 – r705) / (r705 + r665)	Dash and Curran (2004)
NDVI	Normalized Difference Vegetation Index	(r842 – r665) / (r842 + r665)	Kreigler et al. 1989
CI 590	Chlorophyll index 590	(r842 / r560)-1	Gitelson & Merzlyak 1997
GNDVI	Green Normalized Difference Vegetation Index	(r842 - r560) / (r842 + r560)	Gitelson and Merzlyak 1998
PSSRa	Pigment Specific Simple Ratio	R783 / r665	Blackburn 1998
PSNDa	Pigment Specific Normalized Difference	(r783 - r665) / (r783 + r665)	Blackburn 1998
OSAVI	Optimized Soil-Adjusted Vegetation Index	[(1+0.16)*( r842-r665)]/( r842+r665+0.16)	Rondeaux et al. 1996
MCARI	Modified Chlorophyll Absorption in Reflectance index	[(r705 - r665) - 0.2*(r705 - r560)]*(r705 / r665)	Daughtry et al. 2000
TCARI/OSAVI	Transformed Chlorophyll Absorption Ratio Index/OSAVI	3*[(r705-r665)-0.2*(r705- r560)*(r705/r665)]	Haboudane et al. 2002

## REVIEWS

#### Optical vegetation indices for monitoring terrestrial ecosystems globally

Yelu Zeng₀¹, Dalei Hao₀²™, Alfredo Huete³, Benjamin Dechant⁴.5, Joe Berry⁵, Jing M. Chen<sup>7</sup>, Joanna Joiner<sup>8</sup>, Christian Frankenberg 69,10, Ben Bond-Lamberty 11, Youngryel Ryu<sup>®</sup> <sup>12</sup>, Jingfeng Xiao<sup>®</sup> <sup>13</sup>, Ghassem R. Asrar <sup>14</sup> and Min Chen<sup>®</sup> <sup>18</sup>


Abstract | Vegetation indices (VIs), which describe remotely sensed vegetation properties such as photosynthetic activity and canopy structure, are widely used to study vegetation dynamics across scales. However, VI-based results can vary between indices, sensors, quality control measures, compositing algorithms, and atmospheric and sun-target-sensor geometry corrections. These variations make it difficult to draw robust conclusions about ecosystem change and highlight the need for consistent VI application and verification. In this Technical Review, we summarize the history and ecological applications of VIs and the linkages and nconsistencies between them. VIs have been used since the early 1970s and have evolved rapidly with the emergence of new satellite sensors with more spectral channels, new scientific demands and advances in spectroscopy. When choosing VIs, the spectral sensitivity and features of VIs and their suitability for target application should be considered. During data analyses, steps must be taken to minimize the impact of artefacts, VI results should be verified with in situ data when possible and conclusions should be based on multiple sets of indicators. Next-generation VIs with higher signal-to-noise ratios and fewer artefacts will be possible with new satellite missions and integration with emerging vegetation metrics such as solar-induced chlorophyll fluorescence, providing opportunities for studying terrestrial ecosystems globally.

such as soil background, the atmosphere and sun- and controversy related to their use target-sensor geometry2-4. VIs are obtainable at difhave been intensively used in local-scale to global- index (NDVI), the enhanced vegetation index (EVI)

The launch of Earth observation satellites starting in from publicly available remote-sensing data and are 1972 ushered in a new era for global observation and increasingly applied to complex ecological topics, such study of vegetation (FIG. 1), and led to the develop- as vegetation response to long-term climate change 1-10, ment of vegetation indices (VIs). These indices rep-short-term disturbances 11,12 and extreme climate events resent vegetation status conditions through simple The simplicity of VIs, however, can be deceptive. The mathematical combinations or transformations of subtleties in processing and interpretation of results reflectance in two or more spectral channels, while require experience and theoretical background, and minimizing the impacts of other contributing factors, there are many cases of confusion, misinterpretation

ferent scales, from the ground with hand-held spectral
sensing devices to tower-based and airborne sensors
widely used VIs, clarifying and summarizing their useto satellites, and, hence, can provide measurements fulness, relationships, inconsistencies, artefacts and from fine to coarse resolutions. They are also highly limitations. As most VIs are based on reflectance in objective, with no or only minimal assumptions of land the optical wavelengths, we mainly focus on the opticover type and canopy structure. As a result, they cal VIs, We use the normalized difference vegetation

Zeng, Y., Hao, D., Huete, A. et al. Optical vegetation indices for monitoring terrestrial ecosystems globally. Nat Rev Earth Environ 3, 477-493 (2022). https://doi.org/10.1038/s43017-022-00298-5





# How to design your own Spectral index?